

SAFETY DATA SHEET

Methyl Isobutyl Carbinol

1. IDENTIFICATION

Product name: Methyl Isobutyl Carbinol

Recommended use of the chemical and restrictions on use

Identified uses: Chemical additive. Chemical intermediate. Frothing agent.

COMPANY IDENTIFICATION

ALTIVIA Ketones & Additives, LLC 1100 Louisiana Street, Suite 4800 Houston, TX 77002 UNITED STATES

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: CHEMTREC +1 800-424-9300

Local Emergency Contact: 800-424-9300

Emergency Response: For Chemical Emergency Spill, Leak, Fire, Exposure, or Accident Call

CHEMTREC Day or Night

Within USA and Canada: 1-800-424-9300

Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

Web Address: www.ALTIVIA.com

2. HAZARDS IDENTIFICATION

Hazard classification

GHS classification in accordance with 29 CFR 1910.1200 Flammable liquids - Category 3 Eye irritation - Category 2A Specific target organ toxicity - single exposure - Category 3

Label elements Hazard pictograms





Signal word: WARNING!

Date of issue/revision: 9/1/2019 Date of previous issue: 6/26/2018 Page 1 of 12

Hazards

Flammable liquid and vapour.

Causes serious eye irritation.

May cause respiratory irritation.

Precautionary statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ ventilating/ lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/ eye protection/ face protection.

Response

IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

Issue Date: 06/08/2018

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/ attention.

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms: Methyl isobutyl carbinol

This product is a substance.

| Component | CASRN | Concentration |
|--------------------------|----------|---------------|
| Methyl Isobutyl Carbinol | 108-11-2 | > 98.0 % |
| 2,6-Dimethyl-4-heptanone | 108-83-8 | < 2.0 % |
| Methyl isobutyl ketone | 108-10-1 | < 1.0 % |

Date of issue/revision: 9/1/2019 Date of previous issue: 6/26/2018 Page 2 of 12

4. FIRST AID MEASURES

Description of first aid measures General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Skin contact: Wash off with plenty of water. Suitable emergency safety shower facility should be available in work area.

Eye contact: Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

Ingestion: Do not induce vomiting. Call a physician and/or transport to emergency facility immediately.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Maintain adequate ventilation and oxygenation of the patient. May cause asthma-like (reactive airways) symptoms. Bronchodilators, expectorants, antitussives and corticosteroids may be of help. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. The decision of whether to induce vomiting or not should be made by a physician. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Repeated excessive exposure may aggravate preexisting lung disease. Skin contact may aggravate preexisting dermatitis.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Unsuitable extinguishing media: No data available

Special hazards arising from the substance or mixture

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide.

Unusual Fire and Explosion Hazards: Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur.

Date of issue/revision: 9/1/2019 Date of previous issue: 6/26/2018 Page 3 of 12

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Stay upwind. Keep out of low areas where gases (fumes) can accumulate. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Do not use direct water stream. May spread fire. Eliminate ignition sources. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Avoid accumulation of water. Product may be carried across water surface spreading fire or contacting an ignition source.

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Eliminate all sources of ignition in vicinity of spill or released vapor to avoid fire or explosion. Vapor explosion hazard. Keep out of sewers. Isolate area. Refer to section 7, Handling, for additional precautionary measures. Keep unnecessary and unprotected personnel from entering the area. Keep personnel out of low areas. Keep upwind of spill. Ventilate area of leak or spill. No smoking in area. Eliminate all sources of ignition in vicinity of spill or released vapor to avoid fire or explosion. Ground and bond all containers and handling equipment. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Removal of ignition sources: Keep away from sources of ignition.

Dust Control: Not applicable

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up: Small spills: Absorb with materials such as: Sand. Vermiculite. Large spills: Contain spilled material if possible. Collect in suitable and properly labeled containers. Pump with explosion-proof equipment. If available, use foam to smother or suppress. See Section 13, Disposal Considerations, for additional information.

7. HANDLING AND STORAGE

Precautions for safe handling: Use of non-sparking or explosion-proof equipment may be necessary, depending upon the type of operation.

Keep away from heat, sparks and flame. Avoid contact with eyes. Avoid breathing vapor. No smoking, open flames or sources of ignition in handling and storage area. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. Electrically ground and bond all equipment. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION. Wash thoroughly after handling. Keep container closed. Use with adequate ventilation.

Conditions for safe storage: Minimize sources of ignition, such as static build-up, heat, spark or flame.

Storage stability Steel drums. 24 Month Bulk 12 Month

Date of issue/revision: 9/1/2019 Date of previous issue: 6/26/2018 Page 4 of 12

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

| Component | Regulation | Type of listing | Value/Notation |
|--------------------------|------------|-----------------|-------------------|
| Methyl Isobutyl Carbinol | ACGIH | TWA | 25 ppm |
| | ACGIH | STEL | 40 ppm |
| | ACGIH | TWA | SKIN |
| | OSHA Z-1 | TWA | 100 mg/m3 25 ppm |
| | ACGIH | STEL | SKIN |
| | OSHA Z-1 | TWA | SKIN |
| 2,6-Dimethyl-4-heptanone | Dow IHG | TWA | 25 ppm |
| | Dow IHG | STEL | 35 ppm |
| | ACGIH | TWA | 25 ppm |
| | OSHA Z-1 | TWA | 290 mg/m3 50 ppm |
| Methyl isobutyl ketone | ACGIH | TWA | 20 ppm |
| - | ACGIH | STEL | 75 ppm |
| | OSHA Z-1 | TWA | 410 mg/m3 100 ppm |

Biological occupational exposure limits

| Components | CAS-No. | Control parameters | Biological specimen | Sampling time | Permissible concentration | Basis |
|------------------------|----------|------------------------------|---------------------|--|---------------------------|--------------|
| Methyl isobutyl ketone | 108-10-1 | methyl isobutyl ketone | Urine | End of shift (As soon as possible after exposure ceases) | 1 mg/l | ACGIH BEI |

Exposure controls

Engineering controls: Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use chemical goggles. If exposure causes eye discomfort, use a full-face respirator.

Skin protection

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Chlorinated polyethylene. Natural rubber ("latex"). Neoprene. Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl chloride ("PVC" or "vinyl"). Examples of acceptable glove barrier materials include: Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl alcohol ("PVA"). Viton. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Date of issue/revision: 9/1/2019 Date of previous issue: 6/26/2018 Page 5 of 12

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

Issue Date: 06/08/2018

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state Liquid.
Color Colorless
Odor Mild

Odor Threshold

pH

No test data available

No test data available

No test data available

No test data available

Not applicable to liquids

-90 °C (-130 °F) Literature

Boiling point (760 mmHg)

Flash point

No test data available

Evaporation Rate (Butyl Acetate

= 1)

0.43 Literature

Flammability (solid, gas)

Lower explosion limit

Upper explosion limit

Vapor Pressure

No data available

Relative Vapor Density (air = 1) 3.5 Literature

Relative Density (water = 1) 0.807 at 20 °C (68 °F) / 20 °C Literature Water solubility 1.7 % at 20 °C (68 °F) Literature

Partition coefficient: n-

octanol/water

log Pow: 1.57 estimated

Auto-ignition temperature 335 °C (635 °F) at 1,013 hPa *Literature*

Decomposition temperatureNo test data available

Dynamic Viscosity5.2 mPa.s at 20 °C (68 °F) *Literature* **Kinematic Viscosity**6.4 mm2/s at 20 °C (68 °F) *Literature*

Explosive properties Not explosive
Oxidizing properties No Oxidizing
Molecular weight 102.17 g/mol

Molecular formula (CH3)2CHCH2CH(OH)CH3

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: No data available

Chemical stability: Thermally stable at recommended temperatures and pressures.

Possibility of hazardous reactions: Polymerization will not occur.

Date of issue/revision: 9/1/2019 Date of previous issue: 6/26/2018 Page 6 of 12

Conditions to avoid: Exposure to elevated temperatures can cause product to decompose.

Incompatible materials: Avoid contact with: Acid chlorides. Acids. Oxidizers.

Hazardous decomposition products: Decomposition products depend upon temperature, air supply and the presence of other materials.

Issue Date: 06/08/2018

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.

LD50, Rat, 2,590 mg/kg OECD 401 or equivalent

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

LD50, Rabbit, 2,870 mg/kg OECD 402 or equivalent

Acute inhalation toxicity

Prolonged excessive exposure may cause adverse effects. Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs. Symptoms of excessive exposure may be anesthetic or narcotic effects; dizziness and drowsiness may be observed.

LC50, Rat, male and female, 4 Hour, vapour, > 16 mg/l

Skin corrosion/irritation

Brief contact may cause slight skin irritation with local redness.

May cause drying and flaking of the skin.

Serious eye damage/eye irritation

May cause moderate eye irritation.

May cause moderate corneal injury.

Vapor may cause eye irritation experienced as mild discomfort and redness.

Sensitization

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

May cause respiratory irritation.
Route of Exposure: Inhalation
Target Organs: Respiratory Tract

Specific Target Organ Systemic Toxicity (Repeated Exposure)

In animals, effects have been reported on the following organs: Kidney.

Carcinogenicity

For the minor component(s) Has caused cancer in some laboratory animals. However, the relevance of this to humans is unknown.

Date of issue/revision: 9/1/2019 Date of previous issue: 6/26/2018 Page 7 of 12

Teratogenicity

For similar material(s): Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Did not cause birth defects in laboratory animals.

Reproductive toxicity

For similar material(s): In animal studies, did not interfere with reproduction.

Mutagenicity

In vitro genetic toxicity studies were negative.

Aspiration Hazard

May be harmful if swallowed and enters airways.

Carcinogenicity

Component List Classification

Methyl isobutyl ketone IARC Group 2B: Possibly carcinogenic to

humans

ACGIH A3: Confirmed animal carcinogen with

unknown relevance to humans.

Issue Date: 06/08/2018

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, 359 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), semi-static test, 48 Hour, 337 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

EbC50, Pseudokirchneriella subcapitata (green algae), 96 Hour, Biomass, 147 mg/l, OECD Test Guideline 201 or Equivalent

ErC50, Pseudokirchneriella subcapitata (green algae), 96 Hour, Growth rate inhibition, 334 mg/l, OECD Test Guideline 201 or Equivalent

NOEC, Pseudokirchneriella subcapitata (green algae), 96 Hour, Growth rate, 75.5 mg/l

Toxicity to bacteria

EC50, Bacteria, static test, 3 Hour, Respiration rates., > 100 mg/l, activated sludge test (OECD 209)

Persistence and degradability

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready

biodegradability. 10-day Window: Pass Biodegradation: 85 % Exposure time: 28 d

Method: OECD Test Guideline 301F or Equivalent

Theoretical Oxygen Demand: 2.82 mg/mg

Date of issue/revision: 9/1/2019 Date of previous issue: 6/26/2018 Page 8 of 12

Chemical Oxygen Demand: 2.43 mg/mg

Biological oxygen demand (BOD)

| Incubation Time | BOD |
|--------------------|-----------|
| 5 d | 38 - 50 % |
| 10 d | 67 - 72 % |
| 20 d | 67 - 94 % |

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitization: OH radicals Atmospheric half-life: 10 Hour

Method: Estimated.

Bioaccumulative potential

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Issue Date: 06/08/2018

Partition coefficient: n-octanol/water(log Pow): 1.57 estimated

Mobility in soil

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 13 Estimated.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device.

14. TRANSPORT INFORMATION

DO T

Proper shipping name Methyl isobutyl carbinol

UN number UN 2053

Class 3 Packing group III

Classification for SEA transport (IMO-IMDG):

Proper shipping name METHYL ISOBUTYL CARBINOL

UN number UN 2053

Class 3
Packing group III
Marine pollutant No

Transport in bulk Consult IMO regulations before transporting ocean bulk

according to Annex I or II of MARPOL 73/78 and the

IBC or IGC Code

Classification for AIR transport (IATA/ICAO):

Date of issue/revision: 9/1/2019 Date of previous issue: 6/26/2018 Page 9 of 12

Proper shipping name Methyl isobutyl carbinol

UN number UN 2053

Class 3

Packing group III

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

Issue Date: 06/08/2018

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Flammable (gases, aerosols, liquids, or solids)

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

Calculated RQ exceeds reasonably attainable upper limit.

| Components | CASRN | RQ (RCRA Code) |
|------------------------|----------|-------------------|
| Methyl isobutyl ketone | 108-10-1 | 5000 lbs RQ |
| Methyl isobutyl ketone | 108-10-1 | 100 lbs RQ (F003) |
| Methyl isobutyl ketone | 108-10-1 | 5000 lbs RQ |
| Methyl isobutyl ketone | 108-10-1 | 100 lbs RQ (F003) |

Pennsylvania Worker and Community Right-To-Know Act:

The following product components are cited in the Pennsylvania Hazardous Substance List and/or the Pennsylvania Environmental Substance List, and are present at levels which require reporting.

| Components | CASRN |
|--------------------------|----------|
| Methyl Isobutyl Carbinol | 108-11-2 |
| 2,6-Dimethyl-4-heptanone | 108-83-8 |

California Prop. 65

WARNING: This product can expose you to chemicals includingMethyl isobutyl ketone, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System

NFPA

| Health | Flammability | Instability |
|--------|--------------|-------------|
| 1 | 2 | 0 |

Revision

Identification Number: 186466 / A001 / Issue Date: 06/26/2018 / Version: 9.0 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

| 3 | |
|-----------|---|
| ACGIH | USA. ACGIH Threshold Limit Values (TLV) |
| ACGIH BEI | ACGIH - Biological Exposure Indices (BEI) |
| Dow IHG | Dow Industrial Hygiene Guideline |
| OSHA Z-1 | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air |
| | Contaminants |
| SKIN | Absorbed via skin |
| STEL | Short term exposure limit |
| TWA | Time weighted average |

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice: HMIS - Hazardous Materials Identification System: IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration: ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA -Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA -Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations;

Date of issue/revision: 9/1/2019 Date of previous issue: 6/26/2018 Page 11 of 12

UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

ALTIVIA urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer- specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version. US

Date of issue/revision: 9/1/2019 Date of previous issue: 6/26/2018 Page 12 of 12